

Manhattan USB-C Dock/Hub with Card Reader, Ports (x5):

: Ethernet - USB-A (3) and USB-C - 5 Gbps (USB 3.2 Gen1 aka USB 3.0) - With Power Delivery (100W) to USB-C Port (Note additional USB-C wall charger and USB-C cable needed) - Aluminium - Black - Three Year Warranty - Dockingstation - USB-C 3.2 - HDMI - GigE



Gruppe	Kabel / Adapter
Hersteller	Manhattan
Hersteller Art. Nr.	152372
EAN/UPC	0766623152372

Beschreibung

Manhattan USB-C Dock/Hub with Card Reader, Ports (x5): Ethernet, USB-A (3) and USB-C, 5 Gbps (USB 3.2 Gen1 aka USB 3.0), With Power Delivery (100W) to USB-C Port (Note additional USB-C wall charger and USB-C cable needed), Aluminium, Black, Three Year Warranty - Dockingstation - USB-C 3.2 - HDMI - GigE

Hauptmerkmale

Produktbeschreibung	Manhattan USB-C Dock/Hub with Card Reader, Ports (x5): Ethernet, USB-A (3) and USB-C, 5 Gbps (USB 3.2 Gen1 aka USB 3.0), With Power Delivery (100W) to USB-C Port (Note additional USB-C wall charger and USB-C cable needed), Aluminium, Black, Three Year Warranty - Dockingstation - USB-C 3.2 - HDMI - GigE
Produkttyp	Dockingstation
Docking-Schnittstelle	USB-C 3.2
Videoschnittstellen	HDMI
Abmessungen (Breite x Tiefe x Höhe)	11 cm x 4.5 cm x 1.8 cm
Gewicht	80 g
Farbe	Schwarz
Netzwerk	Gigabit Ethernet
Stromversorgung	Gestellte Leistung

Ausführliche Details

	Allgemein
Produkttyp	Dockingstation
Breite	11 cm
Tiefe	4.5 cm
Höhe	1.8 cm
Gewicht	80 g

Farbe	Schwarz
	Video
Details zur max. Auflösung	3840 x 2160 - 30 Hz
	Netzwerk
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
	Erweiterung/Konnektivität
Erweiterungssteckplätze	1 SD-Speicherkarte 1 microSD
Schnittstellen	1 x Audio / Video - HDMI - 19-poliger HDMI Typ A 3 x USB 3.2 Gen 1 - 9-poliger USB Typ A 1 x USB-C mit Stromversorgung (100 W) - 24 pin USB-C 1 x Netzwerk - 10Base-T/100Base-TX/1000Base-T - RJ-45
	Verschiedenes
Enthaltene Kabel	1 x USB-C Kabel - integriert - 30 cm
Leistungsmerkmale	Aluminiumgehäuse, Bus-betrieben, DisplayPort Alt Mode
Kennzeichnung	Plug and Play, FCC, WEEE, RoHS2, HDCP 1.4, USB Power Delivery 3.0
	Systemanforderungen
Erforderliches Betriebssystem	Linux, Microsoft Windows XP / Vista / 7 / 8.1 / 10, Apple MacOS X 10.7.1 oder höher
	Herstellergarantie
Service und Support	Begrenzte Garantie - 3 Jahre
	Umgebungsbedingungen
Min Betriebstemperatur	0 °C
Max. Betriebstemperatur	45 °C

Technische Daten © 1WorldSync. Technische Änderungen und Irrtümer vorbehalten.